



PEDESTAL SERVER

P/N: IP-5600HC2RP

The Nexlink® IP-5600HC2FP is a reliable, scalable, and manageable solution with the versatility to support applications ranging from multipurpose servers in small businesses to workgroup database servers and departmental exchange servers.

SYSTEM

Processor	Intel® Xeon® Processor 5600
Processor Sockets	2
Motherboard	Intel S5520HC
Memory	Support for up to 96GB DDR3; 12 DIMMS
Integrated LAN	2 x Intel Gigabit Ethernet Connections with Intel I/O Acceleration Technology
Integrated Graphics	Server Engine® LLC Pilot II® Controller with 64MB DDR2 memory, 8 MB allocated to graphics
Server Management Support	Intel Server Management Software
I/O Ports and Connectors	6 x USB (2 front, 4 back) 1 x Serial

TOWER

Form Factor	5U Pedestal
Power Supply	Fixed or Redundant
Drive Bays	Up to 10 x 3.5" hot-swap SAS/SATA drives
Front Ports	2 x USB 2.0
PCI Express Slots	1 x PCI-E 2.0 x 8 slot (x 16 mechanical) 3 x PCI-E 2.0 x 8 slot (x 8 mechanical) 1 x PCI-E 1.0 x 4 slot (x 8 mechanical)
Dimensions (w x h x d)	8.6 x 17 x 28.4 inches / 218 x 432 x 721 millimeters

