

PEDESTAL SERVER

P/N: IP-5650BC2

The Nexlink® IP-5650BC2 pedestal server delivers a reliable and cost-effective solution to small- and medium-sized businesses. This 5U pedestal chassis features up to six full-height PCI slots, fixed or hot-swap power supply options, and tool-less features on all drives, bays, and fans for ease of use.

SYSTEM

Processor	Intel® Xeon® Processor 5600
Processor Sockets	2
Motherboard	Intel S5500BC
Memory	Support for up to 32GB DDR3; 8 DIMMS
Integrated LAN	Embedded Intel Dual Gigabit Controller
Integrated Graphics	Server Engine® LLC Pilot II® Controller with 64MB DDR2 memory, 8 MB allocated to graphics
Server Management Support	Intel Server Management Software
Peripheral Interfaces	6 x USB (2 front, 4 back) 1 x Serial

TOWER

Form Factor	5U Pedestal
Power Supply	Fixed or Redundant
Drive Bays	Up to 6 x 3.5" fixed or hot-swap SAS/SATA drives
Front Ports	2 x USB 2.0
PCI Express Slots	2 x PCI-E 2.0 x 8 slot 1 x PCI-E 2.0 x 4 slot (x 8 mechanical) 1 x PCI-E 1.0 x 4 slot
Dimensions (w x h x d)	9.256 x 17.8 x 19 inches / 235 x 452 x 483 millimeters

