



NETWORK VIDEO RECORDER

P/N: XNVR-2012

The Nexlink® X-Vault NVR-2012 Network Video Recorder appliance houses 2 hot-swappable SATA hard drives which are capable of maximum 4TB storage capacity. The unique multi-server monitoring enables the users to monitor up to 120 IP cameras from multiple NVR servers without any extra software.

The XNVR-2012 offers enhanced video search by intelligent video analytics (IVA), including motion detection, foreign object, missing object, out of focus, and camera occlusion. An intuitive user interface is provided for the users to view the monitoring screens, connection and recording status, and the network bandwidth.

SYSTEM

Processor	Intel® Atom™ processor	
Memory	1GB DDRII RAM, 128MB flash (DOM)	
Hard Disk Drive	2 x 3.5" or 2.5" SATA I/II HDD Hot-swappable and lockable tray	
Video Camera Support	Up to 12 Video Channels	
Peripheral Interfaces	3 x USB 2.0 2 x Gigabit RJ-45 Ethernet	1 x VGA reserved 2 x eSATA (back); reserved
Special Features	K-Lock security slot for theft prevention CE, FCC, VCCI, BSMI Certification	
Warranty	1 Year Depot Warranty	

TOWER

Form Factor	Tower
Power Supply	External power adaptor, 60W; input: 110~240V
Dimensions (w x h x d)	4.02 x 5.91 x 8.5 inch / 102 x 150 x 216 mm
Weight	6.44 lb. / 2.92 Kg

FEATURES

- Supports streaming from network cameras and servers
- Real-time monitoring and recording (video/ audio) from multiple network cameras
- Remote management: access and playback recordings by web browser, FTP, and Network Neighborhood anytime, anywhere
- Complete recording features: schedule recording, alarm recording, alarm recording schedule, motion-detection recording, pre-alarm, and post-alarm recordings
- Convenient video backup to external USB storage by one touch auto video backup button

